

View Online at <https://aerobasegroup.com/nsn/5930-00-431-2331>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.984 inches and 1.016 inches

Body Length:

Between 0.612 inches and 0.644 inches

Body Width:

Between 0.390 inches and 0.410 inches

Body Height:

Between 0.290 inches and 0.310 inches

Unthreaded Mounting Hole Diameter:

0.100 inches

Actuator Length:

Between 0.109 inches and 0.141 inches

Actuator Height:

Between 0.318 inches and 0.338 inches

Actuator Width:

Between 0.109 inches and 0.141 inches

Actuator Position-action Relationship:

Left position maintained and right position maintained

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

125.0 ac and 125.0 dc

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

0.500 amperes resistive dc and 0.500 amperes resistive ac

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0