

View Online at <https://aerobasegroup.com/nsn/5930-00-431-5288>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Body Length:

1.094 inches

Body Width:

0.406 inches

Body Height:

0.625 inches

Unthreaded Mounting Hole Diameter:

0.114 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Length:

0.812 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

0.402 inches

Actuator Roller Diameter:

0.168 inches

Actuator Roller Width:

0.168 inches

Maximum Voltage Rating In Volts:

250.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action single switch unit

Switch Release Force:

160.0 grams

Switch Actuating Force:

170.0 grams

Actuator Movement:

Between 0.047 pretravel inches and 0.040 overtravel inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

2 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0