

View Online at <https://aerobasegroup.com/nsn/5930-00-431-8038>

Hazardous Locations/environmental Protection:

Dust resistant and fungus resistant and humidity resistant and salt spray resistant and shock resistant and vibration resistant

Overall Length:

Between 0.490 inches and 0.500 inches

Overall Height:

Between 1.655 inches and 1.735 inches

Overall Width:

Between 1.130 inches and 1.170 inches

Unthreaded Mounting Hole Diameter:

0.089 inches single mounting facility and 0.099 inches single mounting facility

Distance Between Mounting Facility Centers:

0.963 inches single mounting facility and 0.973 inches single mounting facility

Individual Section Quantity:

1

Operating Temperature Range:

-65.0/+100.0 degrees celsius

Mounting Method:

Base single mounting facility and unthreaded hole single mounting facility

Actuator Type:

Thumbwheel single actuator

Features Provided:

Illuminated

Contact Voltage Rating In Volts:

115.0 ac at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

10 single actuator

Terminal Type:

Tab, solder lug and wire loop

Contact Load Current Rating:

125.0 milliamperes resistive load ac at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 single section

Contact Arrangement Truth Table:

Bcd with complement, 1 pole - 10 positions single section

Color:

White single indicator marking

Style Designator:

Rectangular indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0