NSN 5930-00-432-0648

Lock Switch - Page 1 of 1

Fiig: A053a0



View Online at https://aerobasegroup.com/nsn/5930-00-432-0648 **Body Style:** Hole mounted **Hazardous Locations/environmental Protection:** Explosion proof **Body Diameter:** 1.500 inches **Body Length:** 1.640 inches **Center To Center Distance Between Mounting Facilities Parallel To Diameter:** 1.250 inches **Maximum Voltage Rating In Volts:** 150.0 ac and 150.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Unthreaded hole **Nonpile-up Contact Arrangement:** 2 pole, double throw, three positions maintained single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 20.000 milliamperes resistive dc and 20.000 milliamperes resistive ac **Test Data Document:** 81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 6 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:** No