NSN 5930-00-432-2645

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-432-2645

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.906 inches

Shaft Diameter:

0.248 inches single actuator and 0.250 inches single actuator

Shaft Length:

1.156 inches single actuator

Overall Diameter:

1.625 inches

Individual Section Quantity:

1

Operating Tempurature Range:

-50.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

2 single section rear

Mounting Facility Circle Radius:

1.000 inches single mounting facility

Mounting Method:

Threaded hole single mounting facility

Features Provided:

Metallic inclosure

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Contact Voltage Rating In Volts:

29.2 dc at sea level

Mounting Facility Pattern:

Three position circular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

NSN 5930-00-432-2645

Rotary Switch - Page 2 of 2



Contact Switching Action: Breaks before makes single section rear Switch Actuator Positioning Increment: 60.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 5.0 amperes resistive load dc at sea level **Precious Material And Location:** Contact surfaces silver **Precious Material:** Silver Style Designator: Snap or line **Thread Series Designator:** Unc single mounting facility Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A052b0