

View Online at <https://aerobasegroup.com/nsn/5930-00-432-6442>

Hazardous Locations/environmental Protection:

Explosion proof

Actuator Length:

2.500 inches

Actuator Style:

Roller arm

Actuator Roller Diameter:

1.000 inches

Actuator Roller Width:

0.250 inches

Housing Height:

3.250 inches

Housing Length:

9.500 inches

Housing Width:

4.688 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

8.500 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

3.625 inches

Maximum Voltage Rating In Volts:

440.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

2 two circuit, double make, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 1.500 amperes resistive ac

Special Features:

Roller lever cw operation, ccw for by-pass

Test Data Document:

81349-mils901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0