

View Online at <https://aerobasegroup.com/nsn/5930-00-432-6443>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Actuator Length:**

1.188 inches

**Actuator Style:**

Roller arm

**Actuator Roller Diameter:**

1.000 inches

**Actuator Roller Width:**

0.250 inches

**Housing Height:**

3.063 inches

**Housing Width:**

3.250 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

5.250 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

2.375 inches

**Maximum Voltage Rating In Volts:**

440.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Actuator Movement:**

Between 45.0 pretravel degrees and 15.0 overtravel degrees and 5.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

500.000 milliamperes resistive dc and 1.500 amperes resistive ac

**Special Features:**

Roller lever cw and ccw operation

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0