

View Online at <https://aerobasegroup.com/nsn/5930-00-432-6444>

**Hazardous Locations/environmental Protection:**

Explosion proof

**Actuator Length:**

2.500 inches

**Actuator Style:**

Roller arm

**Actuator Roller Diameter:**

1.000 inches

**Actuator Roller Width:**

0.250 inches

**Housing Height:**

3.250 inches

**Housing Length:**

6.375 inches

**Housing Width:**

4.812 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

5.375 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

3.625 inches

**Maximum Voltage Rating In Volts:**

440.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

1 two circuit, double make, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

500.000 milliamperes resistive dc and 1.500 amperes resistive ac

**Special Features:**

Roller lever ccw operation, cw for by-pass

**Test Data Document:**

81349-mils901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A053a0