NSN 5930-00-432-6447



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-432-6447 **Body Style:** Hole mounted **Hazardous Locations/environmental Protection:** Watertight **Actuator Length:** 2.500 inches **Actuator Style:** Roller arm **Actuator Roller Diameter:** 1.000 inches **Actuator Roller Width:** 0.250 inches **Housing Height:** 2.875 inches **Housing Length:** 11.180 inches **Housing Width:** 3.250 inches **Center To Center Distance Between Housing Mounting Facilities Parallel To Length:** 8.375 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 2.375 inches **Maximum Voltage Rating In Volts:** 440.0 ac and 250.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Unthreaded hole **Features Provided:** Actuator seal 2 pole, double throw, one position momentary single switch unit 500.000 milliamperes resistive dc and 1.500 amperes resistive ac

Nonpile-up Contact Arrangement: Contact Load Current Rating At Maximum Rated Voltage: Special Features: Ccw operation **Terminal Type And Quantity:** 6 screw Shelf Life: N/a **Unit Of Measure:**

NSN 5930-00-432-6447

Sensitive Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0