

View Online at <https://aerobasegroup.com/nsn/5930-00-432-6448>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Actuator Length:

3.500 inches

Actuator Style:

Roller arm

Actuator Roller Diameter:

1.500 inches

Actuator Roller Width:

0.313 inches

Housing Height:

3.063 inches

Housing Width:

3.250 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

5.250 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

2.375 inches

Maximum Voltage Rating In Volts:

440.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Actuator Movement:

Between 45.0 pretravel degrees and 15.0 overtravel degrees and 5.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 1.500 amperes resistive ac

Special Features:

Roller lever ccw operation

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0