## NSN 5930-00-432-7641

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-432-7641

**Thread Class:** 2a single mounting facility Thread Length: 0.469 inches single mounting facility **Overall Length:** 3.719 inches **Overall Diameter:** 2.000 inches **Individual Section Quantity: Knob Manufacturer Code:** 82121 **Knob Specificationial Markings:** Arrow sign **Nonturn Device Type:** Slotted bushing at 12: 00 o'clock **Operating Tempurature Range:** -65.0/+125.0 degrees celsius **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section front **Throw Quantity:** 7 each section front **Mounting Method:** Threaded bushing single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.469 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 8 single actuator **Terminal Type:** Tab w/screw **Contact Switching Action:** Breaks before makes each section front **Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

## **NSN 5930-00-432-7641**Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
5.0 amperes resistive load dc at sea level
Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Style Designator:
Tap, circular, bushing mount
Test Data Document:
81349-mil-s-21604 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Uns single mounting facility
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A052b0