

View Online at <https://aerobasegroup.com/nsn/5930-00-432-8986>

Thread Class:

2a single mounting facility

Thread Length:

0.365 inches single mounting facility and 0.395 inches single mounting facility

Overall Length:

3.550 inches

First Flat Length:

0.297 inches single actuator and 0.327 inches single actuator

Flat Height:

0.211 inches single actuator and 0.221 inches single actuator

Shaft Diameter:

0.247 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.730 inches single actuator and 0.770 inches single actuator

Overall Diameter:

1.703 inches

Nonturn Device Radius:

0.531 inches at 3:00 o'clock

Individual Section Quantity:

4

Nonturn Device Type:

Tab at 3:00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

Pole Quantity:

1 4th section rear

Throw Quantity:

23 4th section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

0.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

24 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes 2nd section rear

Switch Actuator Positioning Increment:

15.0 degrees single actuator

Detent Rotational Torque Range:

+1.000/+6.000 inch-pounds single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Test Data Document:

81349-mils3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0