

View Online at <https://aerobasegroup.com/nsn/5930-00-432-9327>

Body Style:

Bushing mount

Bushing Length:

0.470 inches

Body Length:

0.855 inches

Body Width:

0.719 inches

Actuator Length:

Between 0.210 inches and 0.270 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.610 inches and 0.670 inches

Actuator Width:

Between 0.345 inches and 0.405 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

125.0 ac and 30.0 dc

Mounting Surface To Terminal End Distance:

Between 1.017 inches and 1.077 inches

Inclosure Type:

Uninclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc and 1.000 amperes resistive ac

Precious Material And Location:

Contacts gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0