

View Online at <https://aerobasegroup.com/nsn/5930-00-432-9327>

**Body Style:**

Bushing mount

**Bushing Length:**

0.470 inches

**Body Length:**

0.855 inches

**Body Width:**

0.719 inches

**Actuator Length:**

Between 0.210 inches and 0.270 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 0.610 inches and 0.670 inches

**Actuator Width:**

Between 0.345 inches and 0.405 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Maximum Voltage Rating In Volts:**

125.0 ac and 30.0 dc

**Mounting Surface To Terminal End Distance:**

Between 1.017 inches and 1.077 inches

**Inclosure Type:**

Uninclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 500.000 milliamperes inductive dc and 1.000 amperes resistive ac

**Precious Material And Location:**

Contacts gold

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A053a0