## NSN 5930-00-433-6056

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-433-6056
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
Between 9.112 inches and 9.252 inches
Overall Height:
6.750 inches
Overall Width:
6.750 inches
Unthreaded Mounting Hole Diameter:
0.525 inches single mounting facility
Individual Section Quantity:
4
Knob Manufacturer Code:
82121
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 4th section rear
Throw Quantity:
1 3rd section rear
Mounting Facility Circle Radius:
7.953 inches single mounting facility
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
450.0 ac at sea level
Switch Actuator Momentary Position:
Counterclockwise single actuator
Mounting Facility Pattern:
Four position circular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Terminal Type:
Threaded stud
Contact Switching Action:
Breaks before makes 2nd section rear
Switch Actuator Positioning Increment:
00.0 degrees single estuator

90.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

## NSN 5930-00-433-6056

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

200.0 amperes resistive load ac at sea level

**Special Features:** 

First section blank, safety shield mounted on rear

**Style Designator:** 

Tap, circuit selector

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A052b0