

View Online at <https://aerobasegroup.com/nsn/5930-00-434-1938>

**Hazardous Locations/environmental Protection:**

Dusttight and oiltight and watertight

**Overall Length:**

3.812 inches

**Overall Height:**

6.500 inches

**Overall Width:**

3.219 inches

**Body Height:**

5.875 inches

**Unthreaded Mounting Hole Diameter:**

0.203 inches

**Capillary Tube Length:**

72.0 inches

**Bulb Length:**

3.750 inches

**Bulb Diameter:**

0.375 inches

**Longest Horizontal Distance Between Mounting Centers:**

3.000 inches

**Longest Vertical Distance Between Mounting Centers:**

4.500 inches

**Temperature Sensing Element Type:**

Capillary tube-bulb

**Mounting Method:**

Base and unthreaded hole

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

5.0 amperes resistive load first voltage

**Contact Adjustability:**

Actuation point adjustable and deactuation point adjustable

**Contact Adjustment Range:**

+140.00/+290.00 actuation point degrees fahrenheit and +140.00/+290.00 actuation point degrees fahrenheit

**Contact Adjustment Type:**

Internal actuation point screw and internal deactuation point screw

**Contact Voltage Rating In Volts:**

600.0 ac at sea level second voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0