

View Online at <https://aerobasegroup.com/nsn/5930-00-434-1938>

Hazardous Locations/environmental Protection:

Dusttight and oiltight and watertight

Overall Length:

3.812 inches

Overall Height:

6.500 inches

Overall Width:

3.219 inches

Body Height:

5.875 inches

Unthreaded Mounting Hole Diameter:

0.203 inches

Capillary Tube Length:

72.0 inches

Bulb Length:

3.750 inches

Bulb Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

3.000 inches

Longest Vertical Distance Between Mounting Centers:

4.500 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Base and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

5.0 amperes resistive load first voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+140.00/+290.00 actuation point degrees fahrenheit and +140.00/+290.00 actuation point degrees fahrenheit

Contact Adjustment Type:

Internal actuation point screw and internal deactuation point screw

Contact Voltage Rating In Volts:

600.0 ac at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0