

View Online at <https://aerobasegroup.com/nsn/5930-00-434-3181>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Moisture resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

1.940 inches

Body Width:

Between 0.677 inches and 0.697 inches

Body Height:

0.900 inches

Unthreaded Mounting Hole Diameter:

Between 0.139 inches and 0.142 inches

Actuator Style:

Round

Actuator Diameter:

0.094 inches

Actuator Height:

0.100 inches

Actuator Free Position Height:

0.690 inches

Maximum Voltage Rating In Volts:

250.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

10.0 ounces

Switch Actuating Force:

22.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.010 overtravel inches and 0.0075 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

25.000 amperes resistive ac

Terminal Type And Quantity:

3 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0