

View Online at <https://aerobasegroup.com/nsn/5930-00-434-3181>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Moisture resistant

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Body Length:**

1.940 inches

**Body Width:**

Between 0.677 inches and 0.697 inches

**Body Height:**

0.900 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.139 inches and 0.142 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.094 inches

**Actuator Height:**

0.100 inches

**Actuator Free Position Height:**

0.690 inches

**Maximum Voltage Rating In Volts:**

250.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

10.0 ounces

**Switch Actuating Force:**

22.0 ounces

**Actuator Movement:**

Between 0.050 pretravel inches and 0.010 overtravel inches and 0.0075 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

25.000 amperes resistive ac

**Terminal Type And Quantity:**

3 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0