

View Online at <https://aerobasegroup.com/nsn/5930-00-434-9222>

Thread Class:

2a single mounting facility

Thread Length:

0.297 inches single mounting facility and 0.329 inches single mounting facility

Overall Length:

2.688 inches

First Flat Length:

0.234 inches single actuator and 0.266 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.922 inches single actuator and 0.954 inches single actuator

Overall Diameter:

1.297 inches

Individual Section Quantity:

2

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

Pole Quantity:

2 1st section rear

Throw Quantity:

4 1st section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks 2nd section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0