# NSN 5930-00-434-9253

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-434-9253

## **Thread Class:**

2b single mounting facility

## **Overall Length:**

Between 2.087 inches and 2.149 inches

## **Overall Height:**

2.900 inches

## **Overall Width:**

2.900 inches

#### Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

## Shaft Length:

0.437 inches single actuator and 0.499 inches single actuator

Individual Section Quantity:

#### 1

## Longest Horizontal Distance Between Mounting Centers:

1.495 inches single mounting facility and 1.505 inches single mounting facility

## Operating Tempurature Range:

-65.0/+85.0 degrees celsius

## Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 single section rear

#### Throw Quantity:

24 single section rear

## **Mounting Method:**

Threaded hole single mounting facility

#### **Features Provided:**

Variable resistor

## Thready Qty Per Inch (tpi):

32 single mounting facility

## Thread Size:

0.164 inches single mounting facility

## **Contact Voltage Rating In Volts:**

28.0 dc at sea level

## **Mounting Facility Pattern:**

Two position in-line single mounting facility

# Switch Actuator Indexing Position Quantity:

24 single actuator

Shaft Type:

#### Round single actuator

**Terminal Type:** 

Tab, solder lug

# NSN 5930-00-434-9253

Rotary Switch - Page 2 of 2



Contact Switching Action: Breaks before makes single section rear Switch Actuator Positioning Increment: 15.0 degrees single actuator Contact Load Current Rating: 1.0 amperes resistive load dc at sea level Style Designator:

Tap, square frame

#### Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

#### **Demilitarization:**

No

#### Fiig:

A052b0