

View Online at <https://aerobasegroup.com/nsn/5930-00-435-6615>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Submersible

Overall Length:

0.572 inches

Overall Height:

2.158 inches

Overall Width:

0.556 inches

Bushing Length:

0.469 inches

Body Length:

0.572 inches

Body Width:

0.556 inches

Actuator Style:

Round

Actuator Diameter:

0.430 inches

Actuator Height:

0.983 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position no locking action and center position locked in

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

0.706 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 1.000 amperes inductive dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac

Precious Material And Location:

Terminal surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0