## NSN 5930-00-435-9577

Thermostatic Switch - Page 1 of 2

Liquid



View Online at https://aerobasegroup.com/nsn/5930-00-435-9577

| Hazardous Locations/environmental Protection:   |
|---|
| Moisture proof  |
| Overall Length:   |
| 3.750 inches  |
| Overall Height:   |
| 0.812 inches  |
| Overall Width:  |
| 1.938 inches  |
| Body Diameter:  |
| 0.562 inches  |
| Body Length:  |
| 2.281 inches  |
| Tempurature Sensing Element Type:   |
| Bulb  |
| Mounting Method:  |
| Threaded bushing  |
| Features Provided:  |
| Tubing end seal connection  |
| Thready Qty Per Inch (tpi):   |
| 14 single threaded bushing  |
| Contact Action Stimulus:  |
| Increase  |
| Thread Size:  |
| 0.500 inches single threaded bushing  |
| Nonpile-up Contact Arrangement:   |
| 1 pole, double throw, one position momentary  |
| Terminal Type:  |
| Tab, solder lug   |
| Contact Load Current Rating:  |
| 1.0 amperes resistive load second voltage   |
| Contact Adjustability:  |
| Deactuation point adjustable and actuation point adjustable   |
| Contact Adjustment Range:   |
| +3.00/+231.00 actuation point degrees fahrenheit and +0.00/+225.00 deactuation point degrees fahrenheit |
| Contact Adjustment Type:  |
| External deactuation point screw and external actuation point screw                                     |
| Contact Voltage Rating In Volts:  |
| 230.0 ac at sea level first voltage   |
| Frequency In Hertz:   |
| 60.0 second voltage   |
| Media For Which Designed:   |

## NSN 5930-00-435-9577

Thermostatic Switch - Page 2 of 2



| Style Designator:           |
|-----------------------------|
| Rectangular                 |
| Thread Series Designator:   |
| Npt single threaded bushing |
| Shelf Life:                 |
| N/a                         |
| Unit Of Measure:            |
|                             |
| Demilitarization:           |
| No                          |

Fiig: A048b0