

View Online at <https://aerobasegroup.com/nsn/5930-00-436-1863>

Thread Class:

2b all threaded hole

Overall Length:

1.656 inches

Overall Height:

2.875 inches

Overall Width:

1.547 inches

Body Length:

1.656 inches

Distance Between Mounting Facility Centers:

1.750 inches

Capillary Tube Length:

24.000 inches

Bulb Length:

11.625 inches

Bulb Diameter:

0.188 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Bracket and threaded hole

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.138 inches all threaded hole

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

30.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+150.00/+450.00 actuation point degrees fahrenheit and +150.00/+450.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point shaft and external actuation point shaft

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Special Features:

Spring operated lever arm assembly

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0