## NSN 5930-00-436-1984

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-436-1984

## Thread Class:

2b single mounting facility

## Hazardous Locations/environmental Protection:

Moisture proof

## **Overall Length:**

6.782 inches

## **Overall Height:**

2.812 inches

### **Overall Width:**

2.812 inches

## Shaft Length:

2.188 inches single actuator

## Individual Section Quantity:

7

#### Knob Manufacturer Code:

82121

#### Knob Manufacturer Part Number:

А

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section rear

#### Throw Quantity:

5 each section rear

#### **Mounting Facility Circle Radius:**

1.625 inches single mounting facility

#### **Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

#### **Features Provided:**

Actuator knob

## Thready Qty Per Inch (tpi):

24 single mounting facility

## Thread Size:

0.190 inches single mounting facility

## Contact Voltage Rating In Volts:

125.0 ac at sea level

## Mounting Facility Pattern:

Four position circular single mounting facility

## Switch Actuator Indexing Position Quantity:

12 single actuator

### Shaft Type:

Rectangular/square, threaded hole single actuator

# NSN 5930-00-436-1984

Rotary Switch - Page 2 of 2



Square Shaft Size: 0.250 inches single actuator **Terminal Type:** Tab w/screw **Contact Switching Action:** Makes before breaks each section rear **Switch Actuator Positioning Increment:** 30.0 degrees single actuator Switch Actuator Stop Device Type: Adjustable stop single actuator **Contact Load Current Rating:** 7.5 amperes resistive load ac at sea level **Special Features:** Waterproof panel collar and 4 seal screws incl **Style Designator:** Tap, circuit selector **Thread Series Designator:** Unc single mounting facility Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A052b0

---