NSN 5930-00-436-2106

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-436-2106

Hazardous Locations/environmental Protection:
Watertight
Overall Length:
2.000 inches
Overall Height:
2.581 inches
Overall Width:
1.000 inches
Distance Between Mounting Facility Centers:
Between 1.557 inches and 1.567 inches
Pressure Switch Type:
Differential
Mounting Method:
Surface
Thready Qty Per Inch (tpi):
18 all pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
5000.00 pounds per square inch
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained
Contact Load Current Rating:
5.0 amperes resistive load second voltage and 3.0 amperes inductive load second voltage
Contact Stimulus Rating:
70.00 differential point pounds per square inch
Contact Voltage Rating In Volts:
28.0 dc at sea level second voltage
Special Features:
Manual reset button
Thread Series Designator:
Npt all pressure connection
Shelf Life:
N/a
Unit Of Measure:
onit of measure.
Demilitarization:
Deminicanzation.

No

NSN 5930-00-436-2106Pressure Switch - Page 2 of 2



Fiig:

A048b0