

View Online at <https://aerobasegroup.com/nsn/5930-00-436-2474>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.423 inches

Overall Height:

0.330 inches

Body Diameter:

0.650 centimeters

Body Height:

0.325 inches

Unthreaded Mounting Hole Diameter:

0.031 inches

Distance Between Mounting Facility Centers:

0.937 inches

Tempurature Sensing Element Type:

Internal sensor

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

2.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

173.00 actuation point degrees fahrenheit and 162.00 deactuation point degrees fahrenheit and 168.00 deactuation point degrees fahrenheit and 2.00 differential point degrees fahrenheit and 5.00 differential point degrees fahrenheit

Contact Voltage Rating In Volts:

30.0 dc at sea level second voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0