

View Online at <https://aerobasegroup.com/nsn/5930-00-437-8123>

Thread Class:

2a 1st mounting facility

Thread Length:

0.750 inches single mounting facility

Overall Length:

7.489 inches

Overall Height:

1.438 inches

Overall Width:

1.438 inches

First Flat Length:

0.310 inches 2nd actuator

Flat Height:

0.250 inches 1st actuator

Shaft Diameter:

0.216 inches 1st actuator

Shaft Length:

0.495 inches 1st actuator

Unthreaded Mounting Hole Diameter:

0.218 inches 2nd mounting facility

Individual Section Quantity:

6

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

9 each section rear

Mounting Method:

Threaded bushing 1st mounting facility

Features Provided:

Variable resistor

Thread Size:

0.375 inches 1st mounting facility

Contact Voltage Rating In Volts:

300.0 highest ac voltage rating at sea level

Switch Actuator Indexing Position Quantity:

9 single actuator

Shaft Type:

Round, flatted 2nd actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0