

View Online at <https://aerobasegroup.com/nsn/5930-00-437-8123>

**Thread Class:**

2a 1st mounting facility

**Thread Length:**

0.750 inches single mounting facility

**Overall Length:**

7.489 inches

**Overall Height:**

1.438 inches

**Overall Width:**

1.438 inches

**First Flat Length:**

0.310 inches 2nd actuator

**Flat Height:**

0.250 inches 1st actuator

**Shaft Diameter:**

0.216 inches 1st actuator

**Shaft Length:**

0.495 inches 1st actuator

**Unthreaded Mounting Hole Diameter:**

0.218 inches 2nd mounting facility

**Individual Section Quantity:**

6

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

9 each section rear

**Mounting Method:**

Threaded bushing 1st mounting facility

**Features Provided:**

Variable resistor

**Thread Size:**

0.375 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

300.0 highest ac voltage rating at sea level

**Switch Actuator Indexing Position Quantity:**

9 single actuator

**Shaft Type:**

Round, flatted 2nd actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Contact Load Current Rating:**

500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef 1st mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0