

View Online at <https://aerobasegroup.com/nsn/5930-00-438-3405>

**Hazardous Locations/environmental Protection:**

Dusttight

**Overall Length:**

7.750 inches

**Overall Height:**

7.000 inches

**Unthreaded Mounting Hole Diameter:**

0.343 inches

**Longest Horizontal Distance Between Mounting Centers:**

4.000 inches

**Longest Vertical Distance Between Mounting Centers:**

4.000 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Base and unthreaded hole

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

18 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

160.00 pounds per square inch

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Two position diagonal

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

50.0 milliamperes inductive load fourth voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+3.90/+80.00 actuation point pounds per square inch and +0.50/+76.60 deactuation point pounds per square inch

**Contact Adjustment Type:**

Internal deactuation point screw and internal actuation point screw

**Contact Voltage Rating In Volts:**

480.0 ac at sea level first voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Media For Which Designed:**

Gas

**Style Designator:**

Cylindrical w/mounting lugs

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0