

View Online at <https://aerobasegroup.com/nsn/5930-00-439-0870>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Dustproof

Body Diameter:

1.030 inches

Bushing Length:

0.340 inches

Body Length:

2.160 inches

Actuator Length:

1.500 inches

Actuator Style:

Roller arm

Actuator Height:

0.830 inches

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.310 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

145.0 inch-ounces

Switch Actuating Force:

400.0 inch-ounces

Actuator Movement:

Between 13.0 pretravel degrees and 17.0 overtravel degrees and 4.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

1 cable w/connector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0