NSN 5930-00-440-3473

Hazardous Locations/environmental Protection:

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-440-3473

Dustproof
Overall Height:
4.750 inches
Overall Width:
4.750 inches
First Flat Length:
0.625 inches single actuator
Flat Height:
0.312 inches single actuator
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
1.312 inches single actuator
Unthreaded Mounting Hole Diameter:
0.406 inches single mounting facility
Individual Section Quantity:
4
Knob Manufacturer Code:
04009
Longest Horizontal Distance Between Mounting Centers:
3.781 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
3.781 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section front
Throw Quantity:
1 each section front
Mounting Method:
Bracket single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
300.0 ac at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator

Shaft Type:

Round, flatted single actuator

NSN 5930-00-440-3473Rotary Switch - Page 2 of 2



Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
60.0 amperes resistive load dc at sea level
Special Features:
Thd hole and pin type shaft
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A052b0