

View Online at <https://aerobasegroup.com/nsn/5930-00-442-4262>

**Thread Class:**

3b all pressure connection

**Overall Length:**

2.940 inches

**Overall Width:**

3.750 inches

**Body Width:**

2.370 inches

**Unthreaded Mounting Hole Diameter:**

0.210 inches

**Distance Between Mounting Facility Centers:**

3.250 inches

**Pressure Switch Type:**

Differential

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 195.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Hermetically sealed case

**Thready Qty Per Inch (tpi):**

20 all pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

240.00 pounds per square inch gage

**Thread Size:**

0.438 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

1.0 amperes inductive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

14.60 actuation point pounds per square inch and 12.50 deactuation point pounds per square inch and 2.10 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Pressure Connector Type:**

Plain, threaded internal all connections

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular w/bracket

**Thread Series Designator:**

Unf all pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A048b0