

View Online at <https://aerobasegroup.com/nsn/5930-00-442-4262>

Thread Class:

3b all pressure connection

Overall Length:

2.940 inches

Overall Width:

3.750 inches

Body Width:

2.370 inches

Unthreaded Mounting Hole Diameter:

0.210 inches

Distance Between Mounting Facility Centers:

3.250 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 195.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Hermetically sealed case

Thready Qty Per Inch (tpi):

20 all pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

240.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

1.0 amperes inductive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

14.60 actuation point pounds per square inch and 12.50 deactuation point pounds per square inch and 2.10 differential point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded internal all connections

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Unf all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A048b0