

View Online at <https://aerobasegroup.com/nsn/5930-00-442-4924>

**Body Style:**

Bushing/hole mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

0.876 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Overall Width:**

0.346 inches

**Body Length:**

0.876 inches

**Body Width:**

0.346 inches

**Unthreaded Mounting Hole Diameter:**

0.087 inches

**Actuator Style:**

Round

**Actuator Free Position Height:**

0.425 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

17.0 ounces

**Actuator Movement:**

Between 0.050 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0