NSN 5930-00-442-6416

Hazardous Locations/environmental Protection:

Rotary Switch - Page 1 of 2

Dustproof

Square Shaft Size:

0.250 inches single actuator



View Online at https://aerobasegroup.com/nsn/5930-00-442-6416

Overall Length:
5.031 inches
Overall Height:
2.812 inches
Overall Width:
2.812 inches
Shaft Length:
0.781 inches single actuator
Individual Section Quantity:
4
Knob Manufacturer Code:
63743
Longest Horizontal Distance Between Mounting Centers:
2.297 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.297 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section front
Throw Quantity:
8 each section front
Mounting Method:
Bracket single mounting facility
Features Provided:
Actuator knob
Thready Qty Per Inch (tpi):
24 single mounting facility
Thread Size:
0.190 inches single mounting facility
Contact Voltage Rating In Volts:
125.0 ac at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
8 single actuator
Shaft Type:
Rectangular/square, threaded hole single actuator

NSN 5930-00-442-6416Rotary Switch - Page 2 of 2



Tab w/screw Contact Switching Action: Makes before breaks each section front Switch Actuator Positioning Increment: 22.5 degrees single actuator Switch Actuator Stop Device Type:	
Makes before breaks each section front Switch Actuator Positioning Increment: 22.5 degrees single actuator	
Switch Actuator Positioning Increment: 22.5 degrees single actuator	
22.5 degrees single actuator	
Switch Actuator Stop Device Type:	
Adjustable stop single actuator	
Contact Load Current Rating:	
5.0 amperes resistive load ac at sea level	
Style Designator:	
Tap, circuit selector	
Test Data Document:	
81349-mil-s-21604 specification (includes engineering type bulletins, brochures, etc., that reflect specification type	data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type of	data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Thread Series Designator:	
Unc single mounting facility	
Specification Or Standard:	
Sjk type	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A052b0	