NSN 5930-00-442-6433

Rotary Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-00-442-6433 |
|---|
| Thread Class: |
| 2b single mounting facility |
| Hazardous Locations/environmental Protection: |
| Dustproof |
| Overall Length: |
| 8.469 inches |
| Overall Height: |
| 4.125 inches |
| Overall Width: |
| 4.375 inches |
| First Flat Length: |
| 0.500 inches single actuator |
| Flat Height: |
| 0.312 inches single actuator |
| Shaft Diameter: |
| 0.375 inches single actuator |
| Shaft Length: |
| 0.750 inches single actuator |
| Individual Section Quantity: |
| 12 |
| Knob Manufacturer Code: |
| 82121 |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 each section front |
| Throw Quantity: |
| 1 each section front |
| Mounting Facility Circle Radius: |
| 1.609 inches single mounting facility |
| Mounting Method: |
| Bracket single mounting facility and threaded hole single mounting facility |
| Features Provided: |
| Actuator knob |
| Thready Qty Per Inch (tpi): |
| 20 single mounting facility |
| Thread Size: |
| 0.250 inches single mounting facility |

Contact Voltage Rating In Volts:

500.0 ac at sea level

Mounting Facility Pattern:

Four position circular single mounting facility

NSN 5930-00-442-6433Rotary Switch - Page 2 of 2



| Switch Actuator Indexing Position Quantity: |
|--|
| 2 single actuator |
| Shaft Type: |
| Round, flatted, threaded hole single actuator |
| Ferminal Type: |
| Гаb w/screw |
| Contact Switching Action: |
| Breaks before makes each section front |
| Switch Actuator Positioning Increment: |
| 90.0 degrees single actuator |
| Contact Load Current Rating: |
| 30.0 amperes resistive load ac at sea level |
| Style Designator: |
| Гар, circuit selector |
| Test Data Document: |
| 31349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thread Series Designator: |
| Unc single mounting facility |
| Shelf Life: |
| N/a |
| Jnit Of Measure: |
| - |
| Demilitarization: |
| No |
| Filg: |
| A052b0 |
| |
| |