NSN 5930-00-442-8152

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-442-8152

View Online at https://aerobasegroup.com/nsn/5930-00-442-8152
Thread Class:
2b single mounting facility
Overall Length:
2.531 inches
Overall Height:
2.500 inches
Overall Width:
2.500 inches
First Flat Length:
0.750 inches single actuator
Flat Height:
0.219 inches single actuator
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
1.000 inches single actuator
Individual Section Quantity:
2
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
Knob Manufacturer Part Number: A
A
A Knob Specificationial Markings:
A Knob Specificationial Markings: Arrow
A Knob Specificationial Markings: Arrow Longest Horizontal Distance Between Mounting Centers:
A Knob Specificationial Markings: Arrow Longest Horizontal Distance Between Mounting Centers: 1.641 inches single mounting facility
A Knob Specificationial Markings: Arrow Longest Horizontal Distance Between Mounting Centers: 1.641 inches single mounting facility Longest Vertical Distance Between Mounting Centers:
Knob Specificationial Markings: Arrow Longest Horizontal Distance Between Mounting Centers: 1.641 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.641 inches single mounting facility
Knob Specificationial Markings: Arrow Longest Horizontal Distance Between Mounting Centers: 1.641 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.641 inches single mounting facility Switch Contact Basic Design:
Knob Specificationial Markings: Arrow Longest Horizontal Distance Between Mounting Centers: 1.641 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.641 inches single mounting facility Switch Contact Basic Design: Nonpile-up symmetrical
Knob Specificationial Markings: Arrow Longest Horizontal Distance Between Mounting Centers: 1.641 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.641 inches single mounting facility Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity:
Knob Specificationial Markings: Arrow Longest Horizontal Distance Between Mounting Centers: 1.641 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.641 inches single mounting facility Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 each section rear
Knob Specificationial Markings: Arrow Longest Horizontal Distance Between Mounting Centers: 1.641 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.641 inches single mounting facility Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 each section rear Throw Quantity:
Knob Specificationial Markings: Arrow Longest Horizontal Distance Between Mounting Centers: 1.641 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.641 inches single mounting facility Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 each section rear Throw Quantity: 1 each section rear
Knob Specificationial Markings: Arrow Longest Horizontal Distance Between Mounting Centers: 1.641 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.641 inches single mounting facility Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 each section rear Throw Quantity: 1 each section rear Mounting Method:
Knob Specificationial Markings: Arrow Longest Horizontal Distance Between Mounting Centers: 1.641 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.641 inches single mounting facility Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 each section rear Throw Quantity: 1 each section rear Mounting Method: Threaded hole single mounting facility
Knob Specificationial Markings: Arrow Longest Horizontal Distance Between Mounting Centers: 1.641 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.641 inches single mounting facility Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 each section rear Throw Quantity: 1 each section rear Mounting Method: Threaded hole single mounting facility Features Provided:
Knob Specificationial Markings: Arrow Longest Horizontal Distance Between Mounting Centers: 1.641 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.641 inches single mounting facility Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 each section rear Throw Quantity: 1 each section rear Mounting Method: Threaded hole single mounting facility Features Provided: Actuator knob

0.190 inches single mounting facility

NSN 5930-00-442-8152

Rotary Switch - Page 2 of 2

No Fiig: A052b0



Contact Voltage Rating In Volts: 600.0 highest ac voltage rating at sea level **Mounting Facility Pattern:** Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:** 2 single actuator **Shaft Type:** Round, flatted, threaded hole single actuator **Terminal Type:** Tab w/screw **Contact Switching Action:** Breaks before makes each section rear **Switch Actuator Positioning Increment:** 90.0 degrees single actuator **Switch Actuator Stop Device Type:** Adjustable stop single actuator **Contact Load Current Rating:** 5.0 amperes resistive load highest dc voltage rating at sea level **Style Designator:** Tap, circuit selector **Thread Series Designator:** Unc single mounting facility Shelf Life: N/a **Unit Of Measure: Demilitarization:**