## NSN 5930-00-443-9291

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-443-9291

Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
15.781 inches
Overall Height:
6.000 inches
Overall Width:
4.750 inches
Unthreaded Mounting Hole Diameter:
0.406 inches single mounting facility and 0.410 inches single mounting facility
Individual Section Quantity:
11
Knob Manufacturer Code:
82121
Longest Horizontal Distance Between Mounting Centers:
3.781 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
3.781 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
500.0 ac at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Terminal Type:
Tab w/screw
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Contact Load Current Rating:
60.0 amperes resistive load ac at sea level
Style Designator:
Tap, circuit selector
Shelf Life:
N/a
Unit Of Measure:

--

## **NSN 5930-00-443-9291** Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0