

View Online at <https://aerobasegroup.com/nsn/5930-00-444-5544>

**Thread Class:**

2b single mounting facility

**Overall Length:**

Between 5.719 inches and 5.907 inches

**Overall Height:**

2.500 inches

**Overall Width:**

2.250 inches

**Shaft Diameter:**

0.249 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.907 inches single actuator and 0.969 inches single actuator

**Individual Section Quantity:**

4

**Longest Horizontal Distance Between Mounting Centers:**

1.500 inches single mounting facility

**Shortest Horizontal Distance Between Mounting Centers:**

0.750 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.500 inches single mounting facility

**Shortest Vertical Distance Between Mounting Centers:**

0.750 inches single mounting facility

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

17 each section rear

**Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.164 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Mounting Facility Pattern:**

Four position diamond single mounting facility

**Switch Actuator Indexing Position Quantity:**

17 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Switch Actuator Positioning Increment:**

15.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

250.0 milliamperes resistive load dc at sea level

**Style Designator:**

Tap, square frame

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0