

View Online at <https://aerobasegroup.com/nsn/5930-00-444-5544>

Thread Class:

2b single mounting facility

Overall Length:

Between 5.719 inches and 5.907 inches

Overall Height:

2.500 inches

Overall Width:

2.250 inches

Shaft Diameter:

0.249 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.907 inches single actuator and 0.969 inches single actuator

Individual Section Quantity:

4

Longest Horizontal Distance Between Mounting Centers:

1.500 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

0.750 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.500 inches single mounting facility

Shortest Vertical Distance Between Mounting Centers:

0.750 inches single mounting facility

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

17 each section rear

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Four position diamond single mounting facility

Switch Actuator Indexing Position Quantity:

17 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

15.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

250.0 milliamperes resistive load dc at sea level

Style Designator:

Tap, square frame

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0