

View Online at <https://aerobasegroup.com/nsn/5930-00-444-6734>

Body Style:

Bushing mount

Overall Length:

0.572 inches

Overall Height:

1.865 inches

Overall Width:

0.556 inches

Bushing Length:

Between 0.458 inches and 0.562 inches

Body Length:

0.572 inches

Body Width:

0.556 inches

Case Material:

Plastic

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Diameter:

Between 0.240 inches and 0.246 inches

Actuator Height:

Between 0.655 inches and 0.719 inches

Actuator Position-action Relationship:

Down position maintained and center position maintained

Actuator Color:

Natural single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

0.706 inches

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, single throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 1.000 amperes inductive dc and 3.000 amperes resistive ac and 1.000 amperes inductive ac

Precious Material And Location:

Terminal surfaces gold

Test Data Document:

81349-mil-s-8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Specification Data:

96906-ms90311 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0