NSN 5930-00-444-8951

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-444-8951 **Thread Class:** 2a single mounting facility **Overall Length:** 3.860 inches **Overall Height:** 2.380 inches **Overall Width:** 1.500 inches First Flat Length: 0.560 inches single actuator Flat Height: 0.218 inches single actuator **Shaft Diameter:** 0.245 inches single actuator **Shaft Length:** 0.880 inches single actuator **Individual Section Quantity:** 5 **Longest Horizontal Distance Between Mounting Centers:** 1.000 inches single mounting facility **Switch Contact Basic Design:** Pile-up **Mounting Method:** Bracket single mounting facility and threaded stud single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Pile-up Contact Form Arrangement:** 2c each switch each section in-line **Thread Size:** 0.138 inches single mounting facility **Contact Voltage Rating In Volts:** 250.0 highest ac voltage rating at sea level **Mounting Facility Pattern:** Two position in-line single mounting facility **Switch Actuator Indexing Position Quantity:** 2 single actuator **Shaft Type:** Round, flatted single actuator **Terminal Type:** Screw

Switch Actuator Positioning Increment:

30.0 degrees single actuator

NSN 5930-00-444-8951

Rotary Switch - Page 2 of 2



Contact	l oad	Current	Rating:
CUIIIACI	∟∪au	Guileiii	naumu.

5.0 amperes resistive load lowest ac voltage rating at sea level

Style Designator:

In-line, cam actuated

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0