

View Online at <https://aerobasegroup.com/nsn/5930-00-445-0872>

Thread Class:

2b all threaded hole

Overall Length:

2.641 inches

Overall Height:

2.469 inches

Overall Width:

1.000 inches

Body Length:

2.641 inches

Body Height:

2.469 inches

Distance Between Mounting Facility Centers:

0.688 inches

Pressure Switch Type:

Gage

Mounting Method:

Base and threaded hole

Features Provided:

Capillary tube end seal connection

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Decrease

Thread Size:

0.138 inches all threaded hole

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

14.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+100.00/+425.00 actuation point pounds per square inch gage and +100.00/+425.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

185.00 actuation point pounds per square inch and 225.00 deactuation point pounds per square inch and 40.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

115.0 ac at sea level single voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0