

View Online at <https://aerobasegroup.com/nsn/5930-00-445-1624>

**Thread Length:**

0.297 inches single mounting facility and 0.327 inches single mounting facility

**Overall Length:**

Between 2.514 inches and 2.576 inches

**Overall Height:**

Between 1.235 inches and 1.265 inches

**Overall Width:**

Between 0.990 inches and 1.010 inches

**Shaft Diameter:**

0.249 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.594 inches single actuator and 0.656 inches single actuator

**Nonturn Device Radius:**

0.365 inches at 3: 00 o'clock and 0.385 inches at 3: 00 o'clock

**Individual Section Quantity:**

6

**Nonturn Device Type:**

Tab at 3: 00 o'clock

**Operating Temperature Range:**

-65.0/+125.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

6 each section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Switch Actuator Indexing Position Quantity:**

12 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Detent Rotational Torque Range:**

+60.000/+120.000 inch-ounces single actuator

**Style Designator:**

Circular wafer, bushing mount

**Test Data Document:**

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0