NSN 5930-00-445-6803

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-445-6803

Thread Length:
0.375 inches single mounting facility
Overall Length:
1.937 inches
Overall Height:
1.312 inches
Overall Width:
1.250 inches
First Flat Length:
0.375 inches single actuator
Flat Height:
0.219 inches single actuator
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
0.875 inches single actuator
Individual Section Quantity:
3
Mounting Method:
Threaded bushing single mounting facility
Thread Size:
0.375 inches single mounting facility
Contact Voltage Rating In Volts:
Contact Voltage Rating In Volts: 28.0 dc at sea level
28.0 dc at sea level
28.0 dc at sea level Switch Actuator Indexing Position Quantity:
28.0 dc at sea level Switch Actuator Indexing Position Quantity: 2 single actuator
28.0 dc at sea level Switch Actuator Indexing Position Quantity: 2 single actuator Shaft Type:
28.0 dc at sea level Switch Actuator Indexing Position Quantity: 2 single actuator Shaft Type: Round, flatted single actuator
28.0 dc at sea level Switch Actuator Indexing Position Quantity: 2 single actuator Shaft Type: Round, flatted single actuator Terminal Type:
28.0 dc at sea level Switch Actuator Indexing Position Quantity: 2 single actuator Shaft Type: Round, flatted single actuator Terminal Type: Tab, solder lug
28.0 dc at sea level Switch Actuator Indexing Position Quantity: 2 single actuator Shaft Type: Round, flatted single actuator Terminal Type: Tab, solder lug Switch Actuator Positioning Increment:
28.0 dc at sea level Switch Actuator Indexing Position Quantity: 2 single actuator Shaft Type: Round, flatted single actuator Terminal Type: Tab, solder lug Switch Actuator Positioning Increment: 30.0 degrees single actuator
28.0 dc at sea level Switch Actuator Indexing Position Quantity: 2 single actuator Shaft Type: Round, flatted single actuator Terminal Type: Tab, solder lug Switch Actuator Positioning Increment: 30.0 degrees single actuator Contact Load Current Rating:
28.0 dc at sea level Switch Actuator Indexing Position Quantity: 2 single actuator Shaft Type: Round, flatted single actuator Terminal Type: Tab, solder lug Switch Actuator Positioning Increment: 30.0 degrees single actuator Contact Load Current Rating: 5.0 amperes resistive load ac at sea level
28.0 dc at sea level Switch Actuator Indexing Position Quantity: 2 single actuator Shaft Type: Round, flatted single actuator Terminal Type: Tab, solder lug Switch Actuator Positioning Increment: 30.0 degrees single actuator Contact Load Current Rating: 5.0 amperes resistive load ac at sea level Style Designator:
28.0 dc at sea level Switch Actuator Indexing Position Quantity: 2 single actuator Shaft Type: Round, flatted single actuator Terminal Type: Tab, solder lug Switch Actuator Positioning Increment: 30.0 degrees single actuator Contact Load Current Rating: 5.0 amperes resistive load ac at sea level Style Designator: Circular wafer, bushing mount
28.0 dc at sea level Switch Actuator Indexing Position Quantity: 2 single actuator Shaft Type: Round, flatted single actuator Terminal Type: Tab, solder lug Switch Actuator Positioning Increment: 30.0 degrees single actuator Contact Load Current Rating: 5.0 amperes resistive load ac at sea level Style Designator: Circular wafer, bushing mount Thread Series Designator:
28.0 dc at sea level Switch Actuator Indexing Position Quantity: 2 single actuator Shaft Type: Round, flatted single actuator Terminal Type: Tab, solder lug Switch Actuator Positioning Increment: 30.0 degrees single actuator Contact Load Current Rating: 5.0 amperes resistive load ac at sea level Style Designator: Circular wafer, bushing mount Thread Series Designator: Unef single mounting facility

--

NSN 5930-00-445-6803 Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0