

View Online at <https://aerobasegroup.com/nsn/5930-00-446-9124>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Explosion proof

Body Diameter:

0.344 inches

Bushing Length:

0.281 inches

Body Length:

0.547 inches

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Diameter:

0.125 inches

Actuator Height:

0.625 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0