## NSN 5930-00-448-0042

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-448-0042

**Thread Class:** 

2a single mounting facility

**Thread Length:** 

0.375 inches single mounting facility

First Flat Length:

0.380 inches single actuator

Flat Height:

0.210 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.880 inches single actuator

**Individual Section Quantity:** 

1

## **Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:** 

1 single section front

**Throw Quantity:** 

2 single section front

**Mounting Method:** 

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

**Thread Size:** 

0.344 inches single mounting facility

**Contact Voltage Rating In Volts:** 

250.0 highest dc voltage rating at sea level

**Switch Actuator Indexing Position Quantity:** 

2 single actuator

**Shaft Type:** 

Round, flatted single actuator

**Terminal Type:** 

Tab, solder lug

**Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

**Contact Load Current Rating:** 

1.0 amperes resistive load lowest ac voltage rating at sea level

**Thread Series Designator:** 

Uns single mounting facility

Shelf Life:

N/a

## **NSN 5930-00-448-0042** Rotary Switch - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

Demilitarization:

No

Fiig:

A052b0