

View Online at <https://aerobasegroup.com/nsn/5930-00-448-1189>

Body Style:

Bushing/hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Bushing Length:

0.516 inches

Body Length:

1.938 inches

Body Width:

0.688 inches

Body Height:

0.890 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.139 inches

Actuator Style:

Round

Actuator Diameter:

0.328 inches

Actuator Height:

0.859 inches

Actuator Free Position Height:

1.500 inches

Maximum Voltage Rating In Volts:

460.0 ac and 125.0 dc

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 9.0 ounces and 13.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.219 overtravel inches and 0.002 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 15.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A053a0