

View Online at <https://aerobasegroup.com/nsn/5930-00-448-5324>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

1.550 inches

**Overall Height:**

3.160 inches

**Overall Width:**

5.120 inches

**Mounting Slot Width:**

0.203 inches

**Capillary Tube Length:**

24.0 inches

**Bulb Length:**

7.500 inches

**Bulb Diameter:**

0.375 inches

**Longest Horizontal Distance Between Mounting Centers:**

1.266 inches

**Longest Vertical Distance Between Mounting Centers:**

2.000 inches

**Temperature Sensing Element Type:**

Capillary tube-bulb

**Mounting Method:**

Bracket and slot

**Features Provided:**

Capillary tube end seal connection

**Contact Action Stimulus:**

Decrease

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

5.8 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+60.00/+90.00 actuation point degrees fahrenheit and +60.00/+90.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External deactuation point shaft and external actuation point shaft

**Contact Voltage Rating In Volts:**

120.0 ac at sea level single voltage

**Special Features:**

6 slots, 3 slots on opposite of 2 sides and spaced in line 1.000 in. Apart and 1.266 in. Centers

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0